



Renewed range of **thick** thermal paper grades

We are saying goodbye to bisphenol A and bisphenol S! Our grades now offer better resistance properties. The printing performance of both the front and reverse side is optimal. Our selection of thick grades is also wider than before. Check out our non-topcoated and topcoated grades for your ticket and label applications.

Non-topcoated grades for ticket use

NON-BISPHENOL

Key features:

- produced without using bisphenol based developers
- good resistance against heat
- outstanding print performance in UV-flexo
- excellent thermal print result
- standard sensitivity

Topcoated grades for demanding ticket use

NON-PHENOL

Key features:

- produced without using phenol based developers
- good resistance against heat and UV-light
- printable in UV-flexo and UV-offset
- reverse side coated for optimal printing performance
- superior barrier against plasticizers, oil, fat and solvents

TECHNICAL PROPERTIES - NON-TOPCOATED

Grade	Weight (17x22-500 lbs)	Thickness (mils)
AP10KM-H	27.9	3.9
AP11KM-H	30.6	4.3
AP12KM-H	33.8	4.8
AP14KM-H	39.1	5.6
AP17KM-H	47.1	6.8

TECHNICAL PROPERTIES - TOPCOATED

Grade	Weight (17x22-500 lbs)	Thickness (mils)
AP10KT-N	29.3	4.3
AP11KT-N	31.9	4.7
AP12KT-N	35.1	5.2
AP14KT-N	40.4	6.0
AP17KT-N	48.4	7.2